

MAXIMUM SEAL XL4 INJECT + PRO-DRY

AC/REFRIGERATION SERVICE XPRESS INJECT

PART NO.

Part Number	Size
40-101	1.5 to 5 Ton

DESCRIPTION

MAXIMUM SEAL XL4 INJECT + PRO-DRY is the fastest acting dual refrigerant sealer and protectant on the market. This combination product prevents and attacks moisture while neutralizing acids; permanently sealing any small holes. It is formulated to form seals faster by traveling with refrigerant gas instead of oil, and neutralize and convert acids into a synthetic lubricant when combined with the product's moisture remover.

APPLICATIONS

Prevents and eliminates moisture and acid formation in refrigerant lines, which when left untreated can result in instability, burnouts, or complete system failure. Perfect for permanently sealing small holes in A/C condensers, evaporators, fittings, and metal inline sets. After injecting product's formula, leave system charged and running for one day to ensure that the seal has been properly formed.

FEATURES AND BENEFITS

- Fastest Acting Leak Sealant on the Market
- Formulated for a Permanent Seal
- Eliminates Acid
- Removes Moisture
- Prevents Acid
- Compatible With All Refrigerants Except Ammonia

LABEL INFORMATION

MAXIMUM SEAL XL4 INJECT + PRO-DRY is the ideal solution for permanently sealing small holes, and removing and preventing moisture that can cause acid formation in refrigerant lines. Designed to attack and neutralize acids by converting them into a synthetic lubricant compatible with the system's oils. Formulated to form seals faster by traveling with refrigerant gas instead of oil. This product is compatible with all refrigerants except ammonia.

Directions: (If hose is bent or kinked, do not use!) Turn the A/C system on and verify the unit is running. Connect product to the low-side service port of the system. (This is generally the large line). Connect the manifold refrigerant hose to the refrigerant supply tank. Verify the high and low side valves on the manifold are closed before proceeding. Purge the low pressure hose when connecting to product. Open low-side valve and watch for the tube to clear. (This will ONLY take a few seconds!) Turn off low-side manifold valve as soon as the tube is clear. Turn off refrigerant gas. Verify the system is charged to manufacturer's specifications! Disconnect low-side hose from product. Install service port cap. Run the A/C unit at least one hour after installing product. (DO NOT bend or kink hose!)

Dangers: Read and understand the product's label and Safety Data Sheet. May be fatal if swallowed and enters airways. Highly flammable liquid and vapor. May cause skin irritation. Toxic to aquatic life. **DO NOT** use in any manner for which it was not designed. **DO NOT** mix with ammonia. Always wear PPE (Personal Protective Equipment) when servicing HVAC equipment.



⚠ WARNING: This product can expose you to Ethyl Alcohol, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov.

CONTAINS

PLEASE REFER TO SDS FOR PRODUCT'S CONTENTS.

First Aid Measures

Inhalation: If symptoms occur, go to open air and ventilate suspected area. **Immediately call a POISON CENTER or doctor/physician.** **Skin contact:** Wash skin with soap and water. If irritation persists, seek medical attention. **Eye Contact:** Rinse cautiously with water for several minutes. Remove contact lenses if present and easy to do. Continue rinsing. **Immediately call a POISON CENTER or doctor/physician.** **Ingestion:** Do NOT induce vomiting. **Immediately call a POISON CENTER or doctor/physician.**

Precautions

Do NOT handle or use this product until all safety precautions have been read and understood. Keep away from heat/sparks/open flame/hot surfaces – NO SMOKING! Do not breathe dust/fume/gas/mist/vapors/spray. Wash hands and arms thoroughly after handling. Use only outdoors or in a well-ventilated area. Avoid release to the environment. Wear protective gloves/clothing/face/eye protection.

Storage

Keep temperatures below 52°C/125°F. Store in a dry/cool/well ventilated place. Store locked up. Store away from incompatible products.

In Case of Fire

Use dry chemical powder, alcohol-resistant foam or carbon dioxide.

Disposal

Dispose of contents in accordance with local/regional/national regulations. Brass components can be recycled.

Incompatible Products

Heat sources and oxidizers.