

GAS LEAK DETECTOR

LEAK DETECTOR

DESCRIPTION

GAS LEAK DETECTOR is the most sensitive leak detector in the industry. Its bubbles last up to 20 times longer (longer than one hour) than other leading brands. Its formula is perfect for detecting micro sized leaks. Non-toxic and biodegradable.

FEATURES AND BENEFITS

- #1 Leak Detector in the Industry
- Most Sensitive Leak Detector on the Market
- Non-Toxic
- Bubbles Last More than 20 Times Longer
- Biodegradable

SPECIFICATIONS

Form: Clear Blue Liquid | **Odor:** No distinct odor | **Freezing Point:** <32°F (0°C)
Flammability: Not considered a flammable liquid by OSHA | **Vapor Pressure (mm Hg):** 23.8 mmHg @ 77°F (25°C) (Bird Dog); 24 mmHg @ 77°F (25°C) (Low Temp) |
Vapor Density (AIR=1): 1 | **Evaporation Rate:** <0.8 (Slow) | **Specific Gravity (H2O=1):** 1.02 @ 77°F (25°C) (Bird Dog); 0.99 @ 77°F (25°C) (Low Temp) | **pH:** 8 (Bird Dog); 7.5 (Low Temp) | **Solubility in Water:** 100%
Volatility Including Water (%): 99% | **Volatility Organic Compounds (VOC):** 0%

LABEL INFORMATION

GAS LEAK DETECTOR is the ideal solution for pinpointing leaks. Advanced formula detects even the smallest of leaks. It suspends dirt so the particles will not drastically reduce the sensitivity of the product. Suitable for all types of refrigerant, nitrogen and natural gas leaks. Gas Leak Detector is oxygen safe. VOC content is 0%.

Directions for use : Spray or swab product to thoroughly coat surfaces to be checked. Visually inspect for bubbles. Micro leaks will produce a cluster of small bubbles. All surfaces previously coated can be rechecked by wetting areas with water. Turn on system for 5-10 minutes, then visually inspect for vibration leaks.

Dangers: **Read and understand the product's label and Safety Data Sheet.**

Do not take internally. Avoid contact with eyes. Causes eye irritation. May cause skin irritation in rare cases. May cause gastrointestinal irritation.

DO NOT use in any manner for which it was not designed. Always wear safety glasses when when applying product.

Health	0
Flammability	0
Reactivity	0
Personal	A



CONTAINS

GAS LEAK DETECTOR CONTAINS (CAS#) : Water (7732-18-5), Sodium Lauryl Sulfate (151-21-3).

PART NO.

Part Number	Size
N16-11	8 Ounce with Dauber
N16-12	Quart with Trigger Sprayer
N16-13	Gallon

First Aid Measures

Inhalation: Unlikely route of exposure. Move to fresh air.

Skin contact: Wash skin with soap and water. First aid is not normally required.

Eye Contact: Remove contact lenses if present. Flush with water for at least 15 minutes. **See Physician if irritation persists.**

Ingestion: Rinse mouth with water. Do NOT induce vomiting unless directed by medical authority. **Immediately call a POISON CENTER or doctor/physician.**

Precautions

Keep out of reach of children.

Do NOT handle or use this product until all safety precautions have been read and understood. Do not take internally. Avoid contact with eyes. Wash hands and arms thoroughly after handling. Wear protective eye wear such as safety glasses when applying.

Storage

Store in a cool/dry area. Do not store at elevated temperatures.

In Case of Fire

Non-combustible. Not considered flammable. Use appropriate media for surrounding fire.

Disposal

Dispose of contents in accordance with local/regional/national regulations. Non-hazardous. Biodegradable.